



SUPER COOL

Type:	Extreme durable professional exterior paint for the heat of tropical climate.
Classification:	Water based paint thermoreflective for exterior surfaces. Thanks to its high value of SRI (Solar Reflection Index) > 107 , this paint reflects sunlight reducing the surface temperature and cools your homes or buildings. Anti-Algae & Anti-Fungal: long lasting protection against fungus and algae in tropical climates.
Substrate:	On concrete (cement), plaster and brick work surfaces. Perfectly washable and cleanable
Color:	White & pastel color
Chemical composition:	copolymer in emulsion, titanium dioxide, microspheres with controlled granulometric
Specific Weight:	(UNI-EN-ISO 2811-1): 1,020 kg/l \pm 0,05
Viscosity:	(Brookfield A5V20): 10.000 cP \pm 3.000
pH:	8-9
Application methods:	by brush, roller, airless spray or conventional spray.
Dilution:	water may be added up to a maximum of 15% in volume
Spreading rate per coat:	2,5 m ² /l (three coats)
Thickness per coat:	400-500 micron
Drying times:	0,5 h
Recoat times:	6 h
COV:	Cat. A/c (limit UE 40 g/l) <15 g/l
Brightness:	Mat
Surface preparation:	the substrate must be sound, clean, dry and free from dust, oil, grease, laitance etc. New support preparation: new supports must have 4 weeks of maturation; apply ACRYLIC PRIMER or SPECIAL FIXATIVE before. Already painted support: brush and/or scrape the coming off films, dust or wash the surface and apply one coat of SPECIAL FIXATIVE.
Storage:	the shelf life is 3 years if the product is kept in containers with temperature of +5/+30°C away from heat and ignition.

Rev. 1.1 - May 26, 2016

PINTI PAINT - Via Cò de Bruni Levante, 28 - 46019 VIADANA (MN) - ITALY

Tel. ++39 0375 790150 - Fax ++39 0375 790170 – info@pintipaint.com - www.pintipaint.com

Capitale Sociale € 516.000 i.v. - Cod. Fiscale e Part. IVA 00062380209 - Export M/003599 - R.E.A. Mantova N. 127139