



# PINTI

PROFESSIONAL PAINT & TOOLS  
MADE IN ITALY

February 2016

NAME: **FERRUM**  
SERIAL CODE: PPFE8

**CLASSIFICATION:** Decorative covering with micaceous-pearlescent effect applying with brush.  
**KIND OF USE:** The product is suitable as finishing coat for the protection and decoration of inner surface. Excellent feasibility and textural consistency. Suitable for surfaces like plaster and plasterboard.  
**COLOUR:** Gold, silver, bronze, copper base.  
**CHEMICAL COMPOSITION:** acrylic copolymer, pearly micas.  
**SPECIFIC WEIGHT:** 1.390+/-0.050 Kg/lt  
**VISCOSITY OF PRODUCT:** 50.000+/-5.000 cps  
**APPLICATION SYSTEM:** special spalter.  
**DILUTION:** product ready for use, 3-5% water, maximum.  
**MEDIUM OUTPUT** mq/lt for coat: 7 - 8 mq/lt per coat.  
**DRYING:** with air at 20°C with humidity 60%. Application at +5° C minimum.

out of touch	in the depth	time of covering
2-3 h	4-6 h	8-10 h

TABLE DIR.2004/42/CE :  
A/I-BA Product= Decorative effect paint  
Limits UE(2010)=200 gr/lt  
C.O.V. gr/Lt = 100gr/Lt.  
Dilution for application= 5% with water  
C.O.V. (ready to be used) gr/Lt.= Max 100gr/Lt.

**BRILLIANCE:** brilliant/satin  
**PREPARATION OF THE SURFACE:** On new surface in plaster and plasterboard, apply with brush a coat of acrylic primer SPECIAL FIXATIVE. On dry surface, apply a coat with roller of uniform white primer DAS.  
On old surface, brush thoroughly to remove all loose or flaking parts, restoring the missing parts with plaster, then proceed like for new surface. On dry surface, apply a coat with roller of uniform white primer DAS.  
**APPLICATION CYCLES:** When the surface is completely dry, apply a coat of Ferrum with special spalter with stroke and crossed strokes. Wipe the surface with brush without paint distributing the product according to the desired effect.  
It can be applied in different ways, obtaining excellent esthetic results.

**NOTE:** Available in lithographed bucklets of 14 L, 4 L.  
**STABILITY IN STOCK :** 1 year at +5°/+35°C in the original sealed containers. Protect from freezing weather.

All the informations in this card are exact and accurate, as we know, so they must be considered reliable. In any case they can't mean a guarantee from our, as the conditions of its use out of our control.



**Bronze**



# PINTI

PROFESSIONAL PAINT & TOOLS  
MADE IN ITALY

February 2016

NAME: **FERRUM**  
SERIAL CODE: PPFEG

CLASSIFICATION: Decorative covering with micaceous-pearlescent effect applying with brush.  
KIND OF USE: The product is suitable as finishing coat for the protection and decoration of inner surface. Excellent feasibility and textural consistency. Suitable for surfaces like plaster and plasterboard.  
COLOUR: Gold, silver, bronze, copper base.  
CHEMICAL COMPOSITION: acrylic copolymer, pearly micas.  
SPECIFIC WEIGHT: 1.390+/-0.050 Kg/lt  
VISCOSITY OF PRODUCT: 50.000+/-5.000 cps  
APPLICATION SYSTEM: special spalter.  
DILUTION: product ready for use, 3-5% water, maximum.  
MEDIUM OUTPUT mq/lt for coat: 7 - 8 mq/lt per coat.  
DRYING: with air at 20°C with humidity 60%. Application at +5° C minimum.

out of touch	in the depth	time of covering
2-3 h	4-6 h	8-10 h

TABLE DIR.2004/42/CE :  
A/I-BA Product= Decorative effect paint  
Limits UE(2010)=200 gr/lt  
C.O.V. gr/Lt = 100gr/Lt.  
Dilution for application= 5% with water  
C.O.V. (ready to be used) gr/Lt.= Max 100gr/Lt.

BRILLIANCE: brilliant/satin  
PREPARATION OF THE SURFACE: On new surface in plaster and plasterboard, apply with brush a coat of acrylic primer SPECIAL FIXATIVE. On dry surface, apply a coat with roller of uniform white primer DAS.  
On old surface, brush thoroughly to remove all loose or flaking parts, restoring the missing parts with plaster, then proceed like for new surface. On dry surface, apply a coat with roller of uniform white primer DAS.  
APPLICATION CYCLES: When the surface is completely dry, apply a coat of Ferrum with special spalter with stroke and crossed strokes. Wipe the surface with brush without paint distributing the product according to the desired effect.  
It can be applied in different ways, obtaining excellent esthetic results.

NOTE: Available in lithographed bucklets of 14 L, 4 L.  
STABILITY IN STOCK : 1 year at +5°/+35°C in the original sealed containers. Protect from freezing weather.

All the informations in this card are exact and accurate, as we know, so they must be considered reliable. In any case they can't mean a guarantee from our, as the conditions of its use out of our control.



**Gold**





# PINTI

PROFESSIONAL PAINT & TOOLS  
MADE IN ITALY

February 2016

NAME: **FERRUM**  
SERIAL CODE: PPES

**CLASSIFICATION:** Decorative covering with micaceous-pearlescent effect applying with brush.  
**KIND OF USE:** The product is suitable as finishing coat for the protection and decoration of inner surface. Excellent feasibility and textural consistency. Suitable for surfaces like plaster and plasterboard.  
**COLOUR:** Gold, silver, bronze, copper base.  
**CHEMICAL COMPOSITION:** acrylic copolymer, pearly micas.  
**SPECIFIC WEIGHT:** 1.390+/-0.050 Kg/lit  
**VISCOSITY OF PRODUCT:** 50.000+/-5.000 cps  
**APPLICATION SYSTEM:** special spalter.  
**DILUTION:** product ready for use, 3-5% water, maximum.  
**MEDIUM OUTPUT** mq/lit for coat: 7 - 8 mq/lit per coat.  
**DRYING:** with air at 20°C with humidity 60%. Application at +5° C minimum.

out of touch	in the depth	time of covering
2-3 h	4-6 h	8-10 h

TABLE DIR.2004/42/CE :  
A/I-BA Product= Decorative effect paint  
Limits UE(2010)=200 gr/lit  
C.O.V. gr/Lt = 100gr/Lt.  
Dilution for application= 5% with water  
C.O.V. (ready to be used) gr/Lt.= Max 100gr/Lt.

**BRILLIANCE:** brilliant/satin  
**PREPARATION OF THE SURFACE:** On new surface in plaster and plasterboard, apply with brush a coat of acrylic primer SPECIAL FIXATIVE. On dry surface, apply a coat with roller of uniform white primer DAS.  
On old surface, brush thoroughly to remove all loose or flaking parts, restoring the missing parts with plaster, then proceed like for new surface. On dry surface, apply a coat with roller of uniform white primer DAS.  
**APPLICATION CYCLES:** When the surface is completely dry, apply a coat of Ferrum with special spalter with stroke and crossed strokes. Wipe the surface with brush without paint distributing the product according to the desired effect.  
It can be applied in different ways, obtaining excellent esthetic results.

**NOTE:** Available in lithographed bucklets of 14 L, 4 L.  
**STABILITY IN STOCK :** 1 year at +5°/+35°C in the original sealed containers. Protect from freezing weather.

All the informations in this card are exact and accurate, as we know, so they must be considered reliable. In any case they can't mean a guarantee from our, as the conditions of its use out of our control.



*Silver*





# PINTI

PROFESSIONAL PAINT & TOOLS  
MADE IN ITALY

February 2016

NAME: **FERRUM**  
SERIAL CODE: **PPFEC**

**CLASSIFICATION:** Decorative covering with micaceous-pearlescent effect applying with brush.  
**KIND OF USE:** The product is suitable as finishing coat for the protection and decoration of inner surface. Excellent feasibility and textural consistency. Suitable for surfaces like plaster and plasterboard.  
**COLOUR:** Gold, silver, bronze, copper base.  
**CHEMICAL COMPOSITION:** acrylic copolymer, pearly micas.  
**SPECIFIC WEIGHT:** 1.390+/-0.050 Kg/lt  
**VISCOSITY OF PRODUCT:** 50.000+/-5.000 cps  
**APPLICATION SYSTEM:** special spalter.  
**DILUTION:** product ready for use, 3-5% water, maximum.  
**MEDIUM OUTPUT** mq/lt for coat: 7 - 8 mq/lt per coat.  
**DRYING:** with air at 20°C with humidity 60%. Application at +5° C minimum.

out of touch	in the depth	time of covering
2-3 h	4-6 h	8-10 h

TABLE DIR.2004/42/CE :  
A/I-BA Product= Decorative effect paint  
Limits UE(2010)=200 gr/lt  
C.O.V. gr/Lt = 100gr/Lt.  
Dilution for application= 5% with water  
C.O.V. (ready to be used) gr/Lt.= Max 100gr/Lt.

**BRILLIANCE:** brilliant/satin  
**PREPARATION OF THE SURFACE:** On new surface in plaster and plasterboard, apply with brush a coat of acrylic primer **SPECIAL FIXATIVE**. On dry surface, apply a coat with roller of uniform white primer **DAS**.  
On old surface, brush thoroughly to remove all loose or flaking parts, restoring the missing parts with plaster, then proceed like for new surface. On dry surface, apply a coat with roller of uniform white primer **DAS**.  
**APPLICATION CYCLES:** When the surface is completely dry, apply a coat of **Ferrum** with special spalter with stroke and crossed strokes. Wipe the surface with brush without paint distributing the product according to the desired effect.  
It can be applied in different ways, obtaining excellent esthetic results.

**NOTE:** Available in lithographed bucklets of 14 L, 4 L.  
**STABILITY IN STOCK :** 1 year at +5°/+35°C in the original sealed containers. Protect from freezing weather.

All the informations in this card are exact and accurate, as we know, so they must be considered reliable. In any case they can't mean a guarantee from our, as the conditions of its use out of our control.



*Copper*