February 2016



NAME: CRYSTAL SERIAL CODE: PPCRP

CLASSIFICATION: Decorative water metallized covering paint with "materic" effect and crystal of light. KIND OF USE: Ideal to protect and decorating inner surface. Crystal is an excellent metallic fine effect with light crystals and contrast of shiny/matt relief. COLOUR: Pearl. CHEMICAL COMPOSITION: acrylic copolymer modified in water thickness emulsion SPECIFIC WEIGHT: 0.960+/-0.020 Kg/lt VISCOSITY OF PRODUCT: 12500+/-2000 cps APPLICATION: with brush, special spalter. DILUTION: Ready to be used, if necessary with water at 3-5% maximum. MEDIUM OUTPUT mq/lt per coat: 6-7 mq/coat DRYING: with air at 20°C and humidity 60%. Application at +5°C minimum

out of touchin the depthtime of covering30-60minutes2-3h4-5 h

TABLE DIR.2004/42/CE : A/I-BA Product= Decorative paint Limits UE(2010)=200 gr/Lt C.O.V. gr/Lt= 60gr/Lt. Dilution for application= 5% with water C.O.V. (ready to be used) gr/Lt.= Max 60 gr/Lt.

BRILLIANCE: shiny/matt

PREPARATION OF THE SURFACE: On new surface, apply with brush a coat of acrylic primer SPECIAL FIXATIVE. On dry surface, apply a coat with roller of uniform white primer DAS.

On old surface, brush thoroughly to remove all loose or flaking parts, restoring the missing parts with plaster, then proceed like for new surface.

APPLICATION CYCLES: When the surface is prepared apply a coat of Crystal with brush or spalter with short and crossed brush strokes and return with spalter without paint to aggregate materic components to obtain the final effect.

NOTE: Available in lithographed bucklets of 14 L, 4 L, 1L. Please, contact our offices for the feasibility of requested colours.

STABILITY IN STOCK: 1 year at +5°/+35°C in the original sealed containers. Protect from freezing weather.

All the informations in this card are exact and accurate, as we know, so they must be considered reliable. In any case they can't mean a guarantee from our, as the conditions of its use out of our control.



Pearl