



PINTI

PROFESSIONAL PAINT & TOOLS
MADE IN ITALY

February 2016

NAME: FIRENZE
CODE: PPSEC

CLASSIFICATION: Water metallized paint sand effect for interiors with good covering and excellent easy application.

KIND OF USE: Ideal to protect and decorating inner surfaces. Seychelles presents a good metallic materic effect with parts of surface shiny and parts matt, which increase the value of modern and classic interiors.

COLOUR: Pearl, gold, light gold, bronze, copper base.

CHEMICAL COMPOSITION: acrylic copolymer modified in water emulsion

SPECIFIC WEIGHT: 1.250+/-0.500 kg/lit

VISCOSITY OF PRODUCT: 6500 +/- 1500 cps

APPLICATION: brush - spalter

DILUTION: If necessary with water at 3-5%

MEDIUM OUTPUT mq/lit for coat: 8-9 mq/coat

DRYING: with air at 20°C and humidity 60%. Application at +5°C minimum

out of touch	in the depth	time of covering
30-60minutes	2-3h	4-5 h

TABLE DIR. 2004/42/CE:

A/I-BA PRODUCT= Decorative paint

Limits UE(2010)=200 gr/Lt

C.O.V. gr/Lt=60

Dilution for application= 5% with water

C.O.V. (ready to be used) gr/Lt. = Max 60gr/Lt.

BRILLIANCE : opaque

PREPARATION OF THE SURFACE: On new surface, apply with brush a coat of acrylic primer SPECIAL FIXATIVE. On dry surface, apply a coat with roller of uniform white primer DAS.

On old surface, brush thoroughly to remove all loose or flaking parts, restoring the missing parts with plaster, then proceed like for new surface.

APPLICATION CYCLES: When the support is prepared, apply a coat of Seychelles with the special spalter with short and crossed brush strokes and then return with spalter without paint on the surface to distribute the grains of sand in order to obtain the effect like clouds.

STABILITY IN STOCK: 1 year at +5/+35°C in the original sealed containers. Protect from freezing weather.

NOTE: Available in lithographed bucklets of 14 L, 4 L, 1L. Please, contact our offices for the feasibility of requested colours.

All the informations in this card are exact and accurate, as we know, so they must be considered reliable. In any case they can't mean a guarantee from our, as the conditions of its use out of our control.



Copper



PINTI

PROFESSIONAL PAINT & TOOLS
MADE IN ITALY

February 2016

NAME: FIRENZE
CODE: PPSEG

CLASSIFICATION: Water metallized paint sand effect for interiors with good covering and excellent easy application.

KIND OF USE: Ideal to protect and decorating inner surfaces. Seychelles presents a good metallic materic effect with parts of surface shiny and parts matt, which increase the value of modern and classic interiors.

COLOUR: Pearl, gold, light gold, bronze, copper base.

CHEMICAL COMPOSITION: acrylic copolymer modified in water emulsion

SPECIFIC WEIGHT: 1.250+/-0.500 kg/lit

VISCOSITY OF PRODUCT: 6500 +/- 1500 cps

APPLICATION: brush - spalter

DILUTION: If necessary with water at 3-5%

MEDIUM OUTPUT mq/lit for coat: 8-9 mq/coat

DRYING: with air at 20°C and humidity 60%. Application at +5°C minimum

out of touch	in the depth	time of covering
30-60minutes	2-3h	4-5 h

TABLE DIR. 2004/42/CE:

A/I-BA PRODUCT= Decorative paint

Limits UE(2010)=200 gr/Lt

C.O.V. gr/Lt=60

Dilution for application= 5% with water

C.O.V. (ready to be used) gr/Lt. = Max 60gr/Lt.

BRILLIANCE : opaque

PREPARATION OF THE SURFACE: On new surface, apply with brush a coat of acrylic primer SPECIAL FIXATIVE. On dry surface, apply a coat with roller of uniform white primer DAS.

On old surface, brush thoroughly to remove all loose or flaking parts, restoring the missing parts with plaster, then proceed like for new surface.

APPLICATION CYCLES: When the support is prepared, apply a coat of Seychelles with the special spalter with short and crossed brush strokes and then return with spalter without paint on the surface to distribute the grains of sand in order to obtain the effect like clouds.

STABILITY IN STOCK: 1 year at +5/+35°C in the original sealed containers. Protect from freezing weather.

NOTE: Available in lithographed bucklets of 14 L, 4 L, 1L. Please, contact our offices for the feasibility of requested colours.

All the informations in this card are exact and accurate, as we know, so they must be considered reliable. In any case they can't mean a guarantee from our, as the conditions of its use out of our control.



Gold



PINTI

PROFESSIONAL PAINT & TOOLS
MADE IN ITALY

February 2016

NAME: FIRENZE
CODE: PPSEL

CLASSIFICATION: Water metallized paint sand effect for interiors with good covering and excellent easy application.

KIND OF USE: Ideal to protect and decorating inner surfaces. Seychelles presents a good metallic materic effect with parts of surface shiny and parts matt, which increase the value of modern and classic interiors.

COLOUR: Pearl, gold, light gold, bronze, copper base.

CHEMICAL COMPOSITION: acrylic copolymer modified in water emulsion

SPECIFIC WEIGHT: 1.250+/-0.500 kg/lit

VISCOSITY OF PRODUCT: 6500 +/- 1500 cps

APPLICATION: brush - spalter

DILUTION: If necessary with water at 3-5%

MEDIUM OUTPUT mq/lit for coat: 8-9 mq/coat

DRYING: with air at 20°C and humidity 60%. Application at +5°C minimum

out of touch	in the depth	time of covering
30-60minutes	2-3h	4-5 h

TABLE DIR. 2004/42/CE:

A/I-BA PRODUCT= Decorative paint

Limits UE(2010)=200 gr/Lt

C.O.V. gr/Lt=60

Dilution for application= 5% with water

C.O.V. (ready to be used) gr/Lt. = Max 60gr/Lt.

BRILLIANCE : opaque

PREPARATION OF THE SURFACE: On new surface, apply with brush a coat of acrylic primer SPECIAL FIXATIVE. On dry surface, apply a coat with roller of uniform white primer DAS.

On old surface, brush thoroughly to remove all loose or flaking parts, restoring the missing parts with plaster, then proceed like for new surface.

APPLICATION CYCLES: When the support is prepared, apply a coat of Seychelles with the special spalter with short and crossed brush strokes and then return with spalter without paint on the surface to distribute the grains of sand in order to obtain the effect like clouds.

STABILITY IN STOCK: 1 year at +5/+35°C in the original sealed containers. Protect from freezing weather.

NOTE: Available in lithographed bucklets of 14 L, 4 L, 1L. Please, contact our offices for the feasibility of requested colours.

All the informations in this card are exact and accurate, as we know, so they must be considered reliable. In any case they can't mean a guarantee from our, as the conditions of its use out of our control.



Light Gold



PINTI

PROFESSIONAL PAINT & TOOLS
MADE IN ITALY

February 2016

NAME: FIRENZE
CODE: PPSEB

CLASSIFICATION: Water metallized paint sand effect for interiors with good covering and excellent easy application.

KIND OF USE: Ideal to protect and decorating inner surfaces. Seychelles presents a good metallic materic effect with parts of surface shiny and parts matt, which increase the value of modern and classic interiors.

COLOUR: Pearl, gold, light gold, bronze, copper base.

CHEMICAL COMPOSITION: acrylic copolymer modified in water emulsion

SPECIFIC WEIGHT: 1.250+/-0.500 kg/lit

VISCOSITY OF PRODUCT: 6500 +/- 1500 cps

APPLICATION: brush - spalter

DILUTION: If necessary with water at 3-5%

MEDIUM OUTPUT mq/lit for coat: 8-9 mq/coat

DRYING: with air at 20°C and humidity 60%. Application at +5°C minimum

out of touch in the depth time of covering

30-60minutes 2-3h 4-5 h

TABLE DIR. 2004/42/CE:

A/I-BA PRODUCT= Decorative paint

Limits UE(2010)=200 gr/Lt

C.O.V. gr/Lt=60

Dilution for application= 5% with water

C.O.V. (ready to be used) gr/Lt. = Max 60gr/Lt.

BRILLIANCE : opaque

PREPARATION OF THE SURFACE: On new surface, apply with brush a coat of acrylic primer SPECIAL FIXATIVE. On dry surface, apply a coat with roller of uniform white primer DAS.

On old surface, brush thoroughly to remove all loose or flaking parts, restoring the missing parts with plaster, then proceed like for new surface.

APPLICATION CYCLES: When the support is prepared, apply a coat of Seychelles with the special spalter with short and crossed brush strokes and then return with spalter without paint on the surface to distribute the grains of sand in order to obtain the effect like clouds.

STABILITY IN STOCK: 1 year at +5/+35°C in the original sealed containers. Protect from freezing weather.

NOTE: Available in lithographed bucklets of 14 L, 4 L, 1L. Please, contact our offices for the feasibility of requested colours.

All the informations in this card are exact and accurate, as we know, so they must be considered reliable. In any case they can't mean a guarantee from our, as the conditions of its use out of our control.



Bronze



PINTI

PROFESSIONAL PAINT & TOOLS
MADE IN ITALY

February 2016

NAME: FIRENZE
CODE: PPSEP

CLASSIFICATION: Water metallized paint sand effect for interiors with good covering and excellent easy application.

KIND OF USE: Ideal to protect and decorating inner surfaces. Seychelles presents a good metallic materic effect with parts of surface shiny and parts matt, which increase the value of modern and classic interiors.

COLOUR: Pearl, gold, light gold, bronze, copper base.

CHEMICAL COMPOSITION: acrylic copolymer modified in water emulsion

SPECIFIC WEIGHT: 1.250+/-0.500 kg/lit

VISCOSITY OF PRODUCT: 6500 +/- 1500 cps

APPLICATION: brush - spalter

DILUTION: If necessary with water at 3-5%

MEDIUM OUTPUT mq/lit for coat: 8-9 mq/coat

DRYING: with air at 20°C and humidity 60%. Application at +5°C minimum

out of touch in the depth time of covering

30-60minutes 2-3h 4-5 h

TABLE DIR. 2004/42/CE:

A/I-BA PRODUCT= Decorative paint

Limits UE(2010)=200 gr/Lt

C.O.V. gr/Lt=60

Dilution for application= 5% with water

C.O.V. (ready to be used) gr/Lt. = Max 60gr/Lt.

BRILLIANCE : opaque

PREPARATION OF THE SURFACE: On new surface, apply with brush a coat of acrylic primer SPECIAL FIXATIVE. On dry surface, apply a coat with roller of uniform white primer DAS.

On old surface, brush thoroughly to remove all loose or flaking parts, restoring the missing parts with plaster, then proceed like for new surface.

APPLICATION CYCLES: When the support is prepared, apply a coat of Seychelles with the special spalter with short and crossed brush strokes and then return with spalter without paint on the surface to distribute the grains of sand in order to obtain the effect like clouds.

STABILITY IN STOCK: 1 year at +5/+35°C in the original sealed containers. Protect from freezing weather.

NOTE: Available in lithographed bucklets of 14 L, 4 L, 1L. Please, contact our offices for the feasibility of requested colours.

All the informations in this card are exact and accurate, as we know, so they must be considered reliable. In any case they can't mean a guarantee from our, as the conditions of its use out of our control.



Pearl