



PINTI

PROFESSIONAL PAINT & TOOLS
MADE IN ITALY

February 2016

NAME: ROMA
SERIAL CODE: PPALC

CLASSIFICATION: Acrylic metallized water finish for interiors with excellent covering and brush application.
KIND OF USE: To protect and decorate inner surfaces. Alicante presents a good metallic-glazed effect with parts of surface shiny and parts matt, which increase the value of modern and classic interiors.

COLOUR: Gold, Bronze, Copper, Light gold and pearl.

CHEMICAL COMPOSITION: acrylic copolymer modified in water emulsion

SPECIFIC WEIGHT: 1.100+/-0.020 Kg/lit

VISCOSITY OF PRODUCT: 7000+/-1500 cps

APPLICATION: with brush or special spalter

DILUTION: Ready to be used, if necessary with water at 3-5% maximum

MEDIUM OUTPUT mq/lit per coat: 9-10mq/coat

DRYING: with air at 20°C and humidity 60%. Application at +5° C minimum

| out of touch | in the depth | time of covering |
|--------------|--------------|------------------|
| 30-60minutes | 2-3h | 4-5 h |

TABLE DIR.2004/42/CE :

A/I-BA Product= Decorative paint

Limits UE(2010)=200 gr/Lt

C.O.V. gr/Lt=30gr/Lt.

Dilution for application= 5% with water

C.O.V. (ready to be used) gr/Lt.= Max 30gr/Lt.

BRILLIANCE: glazed

PREPARATION OF THE SURFACE: On new surface, apply with brush a coat of acrylic primer SPECIAL FIXATIVE.

On dry surface, apply a coat with roller of uniform white primer DAS.

On old surface, brush thoroughly to remove all loose or flaking parts, restoring the missing parts with plaster, then proceed like for new surface.

APPLICATION CYCLES: When the surface is perfectly prepared, apply a coat of Alicante with the special spalter with short and crossed brush strokes. Wipe the surface with exhaust spalter to distribute the excess material. To increase the final brilliant effect apply a second coat of Alicante, with the same process.

NOTE: Available in lithographed bucklets of 14 L, 4 L, 1L. Please, contact our offices for the feasibility of requested colours.

STABILITY IN STOCK : 1 year at +5° / +35°C in the original sealed containers. Protect from freezing weather.

All the informations in this card are exact and accurate, as we know, so they must be considered reliable. In any case they can't mean a guarantee from our, as the conditions of its use out of our control.



Copper



PINTI

PROFESSIONAL PAINT & TOOLS
MADE IN ITALY

February 2016

NAME: ROMA
SERIAL CODE: PPALG

CLASSIFICATION: Acrylic metallized water finish for interiors with excellent covering and brush application.
KIND OF USE: To protect and decorate inner surfaces. Alicante presents a good metallic-glazed effect with parts of surface shiny and parts matt, which increase the value of modern and classic interiors.

COLOUR: Gold, Bronze, Copper, Light gold and pearl.

CHEMICAL COMPOSITION: acrylic copolymer modified in water emulsion

SPECIFIC WEIGHT: 1.100+/-0.020 Kg/lit

VISCOSITY OF PRODUCT: 7000+/-1500 cps

APPLICATION: with brush or special spalter

DILUTION: Ready to be used, if necessary with water at 3-5% maximum

MEDIUM OUTPUT mq/lit per coat: 9-10mq/coat

DRYING: with air at 20°C and humidity 60%. Application at +5° C minimum

| out of touch | in the depth | time of covering |
|--------------|--------------|------------------|
| 30-60minutes | 2-3h | 4-5 h |

TABLE DIR.2004/42/CE :

A/I-BA Product= Decorative paint

Limits UE(2010)=200 gr/Lt

C.O.V. gr/Lt=30gr/Lt.

Dilution for application= 5% with water

C.O.V. (ready to be used) gr/Lt.= Max 30gr/Lt.

BRILLIANCE: glazed

PREPARATION OF THE SURFACE: On new surface, apply with brush a coat of acrylic primer SPECIAL FIXATIVE.

On dry surface, apply a coat with roller of uniform white primer DAS.

On old surface, brush thoroughly to remove all loose or flaking parts, restoring the missing parts with plaster, then proceed like for new surface.

APPLICATION CYCLES: When the surface is perfectly prepared, apply a coat of Alicante with the special spalter with short and crossed brush strokes. Wipe the surface with exhaust spalter to distribute the excess material. To increase the final brilliant effect apply a second coat of Alicante, with the same process.

NOTE: Available in lithographed bucklets of 14 L, 4 L, 1L. Please, contact our offices for the feasibility of requested colours.

STABILITY IN STOCK : 1 year at +5°/ +35°C in the original sealed containers. Protect from freezing weather.

All the informations in this card are exact and accurate, as we know, so they must be considered reliable. In any case they can't mean a guarantee from our, as the conditions of its use out of our control.



Gold



PINTI

PROFESSIONAL PAINT & TOOLS
MADE IN ITALY

February 2016

NAME: ROMA
SERIAL CODE: PPALL

CLASSIFICATION: Acrylic metallized water finish for interiors with excellent covering and brush application.
KIND OF USE: To protect and decorate inner surfaces. Alicante presents a good metallic-glazed effect with parts of surface shiny and parts matt, which increase the value of modern and classic interiors.

COLOUR: Gold, Bronze, Copper, Light gold and pearl.

CHEMICAL COMPOSITION: acrylic copolymer modified in water emulsion

SPECIFIC WEIGHT: 1.100+/-0.020 Kg/lit

VISCOSITY OF PRODUCT: 7000+/-1500 cps

APPLICATION: with brush or special spalter

DILUTION: Ready to be used, if necessary with water at 3-5% maximum

MEDIUM OUTPUT mq/lit per coat: 9-10mq/coat

DRYING: with air at 20°C and humidity 60%. Application at +5° C minimum

| out of touch | in the depth | time of covering |
|--------------|--------------|------------------|
| 30-60minutes | 2-3h | 4-5 h |

TABLE DIR.2004/42/CE :

A/I-BA Product= Decorative paint

Limits UE(2010)=200 gr/Lt

C.O.V. gr/Lt=30gr/Lt.

Dilution for application= 5% with water

C.O.V. (ready to be used) gr/Lt.= Max 30gr/Lt.

BRILLIANCE: glazed

PREPARATION OF THE SURFACE: On new surface, apply with brush a coat of acrylic primer SPECIAL FIXATIVE.

On dry surface, apply a coat with roller of uniform white primer DAS.

On old surface, brush thoroughly to remove all loose or flaking parts, restoring the missing parts with plaster, then proceed like for new surface.

APPLICATION CYCLES: When the surface is perfectly prepared, apply a coat of Alicante with the special spalter with short and crossed brush strokes. Wipe the surface with exhaust spalter to distribute the excess material. To increase the final brilliant effect apply a second coat of Alicante, with the same process.

NOTE: Available in lithographed bucklets of 14 L, 4 L, 1L. Please, contact our offices for the feasibility of requested colours.

STABILITY IN STOCK : 1 year at +5° / +35°C in the original sealed containers. Protect from freezing weather.

All the informations in this card are exact and accurate, as we know, so they must be considered reliable. In any case they can't mean a guarantee from our, as the conditions of its use out of our control.



Light Gold



PINTI

PROFESSIONAL PAINT & TOOLS
MADE IN ITALY

February 2016

NAME: ROMA
SERIAL CODE: PPALB

CLASSIFICATION: Acrylic metallized water finish for interiors with excellent covering and brush application.
KIND OF USE: To protect and decorate inner surfaces. Alicante presents a good metallic-glazed effect with parts of surface shiny and parts matt, which increase the value of modern and classic interiors.

COLOUR: Gold, Bronze, Copper, Light gold and pearl.

CHEMICAL COMPOSITION: acrylic copolymer modified in water emulsion

SPECIFIC WEIGHT: 1.100+/-0.020 Kg/lit

VISCOSITY OF PRODUCT: 7000+/-1500 cps

APPLICATION: with brush or special spalter

DILUTION: Ready to be used, if necessary with water at 3-5% maximum

MEDIUM OUTPUT mq/lit per coat: 9-10mq/coat

DRYING: with air at 20°C and humidity 60%. Application at +5° C minimum

| out of touch | in the depth | time of covering |
|--------------|--------------|------------------|
| 30-60minutes | 2-3h | 4-5 h |

TABLE DIR.2004/42/CE :

A/I-BA Product= Decorative paint

Limits UE(2010)=200 gr/Lt

C.O.V. gr/Lt=30gr/Lt.

Dilution for application= 5% with water

C.O.V. (ready to be used) gr/Lt.= Max 30gr/Lt.

BRILLIANCE: glazed

PREPARATION OF THE SURFACE: On new surface, apply with brush a coat of acrylic primer SPECIAL FIXATIVE.

On dry surface, apply a coat with roller of uniform white primer DAS.

On old surface, brush thoroughly to remove all loose or flaking parts, restoring the missing parts with plaster, then proceed like for new surface.

APPLICATION CYCLES: When the surface is perfectly prepared, apply a coat of Alicante with the special spalter with short and crossed brush strokes. Wipe the surface with exhaust spalter to distribute the excess material. To increase the final brilliant effect apply a second coat of Alicante, with the same process.

NOTE: Available in lithographed bucklets of 14 L, 4 L, 1L. Please, contact our offices for the feasibility of requested colours.

STABILITY IN STOCK : 1 year at +5°/ +35°C in the original sealed containers. Protect from freezing weather.

All the informations in this card are exact and accurate, as we know, so they must be considered reliable. In any case they can't mean a guarantee from our, as the conditions of its use out of our control.



Bronze



PINTI

PROFESSIONAL PAINT & TOOLS
MADE IN ITALY

February 2016

NAME: ROMA
SERIAL CODE: PPALP

CLASSIFICATION: Acrylic metallized water finish for interiors with excellent covering and brush application.

KIND OF USE: To protect and decorate inner surfaces. Alicante presents a good metallic-glazed effect with parts of surface shiny and parts matt, which increase the value of modern and classic interiors.

COLOUR: Gold, Bronze, Copper, Light gold and pearl.

CHEMICAL COMPOSITION: acrylic copolymer modified in water emulsion

SPECIFIC WEIGHT: 1.100+/-0.020 Kg/lit

VISCOSITY OF PRODUCT: 7000+/-1500 cps

APPLICATION: with brush or special spalter

DILUTION: Ready to be used, if necessary with water at 3-5% maximum

MEDIUM OUTPUT mq/lit per coat: 9-10mq/coat

DRYING: with air at 20°C and humidity 60%. Application at +5° C minimum

| out of touch | in the depth | time of covering |
|--------------|--------------|------------------|
| 30-60minutes | 2-3h | 4-5 h |

TABLE DIR.2004/42/CE :

A/I-BA Product= Decorative paint

Limits UE(2010)=200 gr/Lt

C.O.V. gr/Lt=30gr/Lt.

Dilution for application= 5% with water

C.O.V. (ready to be used) gr/Lt.= Max 30gr/Lt.

BRILLIANCE: glazed

PREPARATION OF THE SURFACE: On new surface, apply with brush a coat of acrylic primer SPECIAL FIXATIVE.

On dry surface, apply a coat with roller of uniform white primer DAS.

On old surface, brush thoroughly to remove all loose or flaking parts, restoring the missing parts with plaster, then proceed like for new surface.

APPLICATION CYCLES: When the surface is perfectly prepared, apply a coat of Alicante with the special spalter with short and crossed brush strokes. Wipe the surface with exhaust spalter to distribute the excess material. To increase the final brilliant effect apply a second coat of Alicante, with the same process.

NOTE: Available in lithographed buckets of 14 L, 4 L, 1L. Please, contact our offices for the feasibility of requested colours.

STABILITY IN STOCK : 1 year at +5°/ +35°C in the original sealed containers. Protect from freezing weather.

All the informations in this card are exact and accurate, as we know, so they must be considered reliable. In any case they can't mean a guarantee from our, as the conditions of its use out of our control.



Pearl