February 2016



NAME: STAR

SERIAL CODE: PPCOW

CLASSIFICATION: Decorative satin covering with crystal light and glitters.

KIND OF USE: To protect and decorate inner surfaces. It lets obtain surfaces with particular light effects with

silver crystals it is easy to apply and it is ideal for plaster, plaster board and plaster finishing.

COLOUR: White and neutral white with silver glitters.

CHEMICAL COMPOSITION: acrylic copolymer modified in water emulsion

SPECIFIC WEIGHT: 1.400+/-0.150 Kg/lt

APPLICATION: with brush, roller. DILUTION: with water at 3-5%

MEDIUM OUTPUT mq/lt per coat: 7-8 mq/two coat

DRYING: with air at 20°C and humidity 60%. Application at +5° C minimum

out of touch in the depth time of covering
4-5 h 6-8 h 6-8 h

TABLE DIR.2004/42/CE:

A/I-BA Product= Decorative paint
Limits UE(2010)=200 gr/Lt
C.O.V. gr/Lt=130gr/Lt.
Dilution for application= 5% with water
C.O.V. (ready to be used) gr/Lt.= Max 130gr/Lt.

BRILLIANCE: satin

PREPARATION OF THE SURFACE: If the surface is perfectly stabilized, apply a coat of acrylic primer SPECIAL FIXATIVE and then a coat with roller of uniform white primer DAS.

APPLICATION CYCLES: When the surface is perfectly prepared, apply a coat of Comete New with the wanted colour with brush or roller with short and crossed brush strokes. To obtain more concentration of crystals, after 3-4 hours, apply a second coat of Comete new with the same process.

NOTE: Available in lithographed bucklets of 14 L, 4 L, 1L. Please, contact our offices for the feasibility of requested colours.

STABILITY IN STOCK: 1 year at +5°/ +35°C in the original sealed containers. Protect from freezing weather.

All the informations in this card are exact and accurate, as we know, so they must be considered reliable. In any case they can't mean a guarantee from our, as the conditions of its use out of our control.



44 Star