



NAME: TINTORETTO STUCCO
CODE: PPTIW005

CLASSIFICATION: Mineral stucco of lime paste with marble micronized powders. *Without any V.O.C.*
KIND OF USE : For the decoration and protection of inner historic and modern surfaces of particularly valuable. It presents a spatula final effect with light-dark tones and gloss-matt.

COLOUR : white

BRILLIANCE : matt

CHEMICAL COMPOSITION : Lime paste with long maturation, marble powders and selected inerts.

SPECIFIC WEIGHT: 1.560+/-0.050 kg/lit

APPLICATION SYSTEM : trowel, inox spatula

DILUTION : ready to be used

MEDIUM OUTPUT mq/kg: 500-700 gr/mq for 2 coats

DRYING : with air at 20°C with humidity 60 %

out of touch in the depth time of covering

2h 2-3 days 6-8 h

MINIMUM TEMPERATURE FOR APPLICATION: +5 °C

TABLE DIR.2004/42/CE:

A/I-BA Product= Decorative paint.

Limits UE(2010)= 200 gr/Lt

C.O.V. gr/Lt = 20 gr/Lt.

C.O.V. (ready to be used) gr/Lt.= Max 20 gr/Lt.

PREPARATION OF THE SURFACE: On new support in plaster, drywall with the surface perfectly stabilized, apply a coat of acrylic primer SPECIAL FIXATIVE and then a coat with roller of uniform white primer Pinti.

On old surface, brush thoroughly to remove all loose or flaking parts, restoring the missing parts with plaster, then proceed like for new surface.

APPLICATION CYCLES: When the surface is perfectly prepared apply a coat of Tintoretto Stucco new with inox spatula to distribute the product on all the surface. Then one or two coats with trowel or inox spatula with the desired effect. On dry surface, but not completely dried, pass over the surface with inox spatula without paint, with a lightly pressure, to obtain the desired effect.

STABILITY IN STOCK: 1 year at +5°C/35°C in the original sealed containers. Protect from freezing weather.

NOTE: available in bucketlets of 5 kg.

All the informations in this card are exact and accurate, as we know, so they must be considered reliable. In any case they can't mean a guarantee from our, as the conditions of its use out of our control.

